

OLYMPIAN™

GEP26SP1

*Diesel Generator Set
Exclusively from your Caterpillar® dealer*



Output Ratings		
Generating Set Model	Prime*	Standby*
220-240V, 50 Hz	24.0 kVA	26.0 kVA
	24.0 kW	26.0 kW
240V, 60 Hz	27.0 kVA	30.0 kVA
	27.0 kW	30.0 kW

* Refer to ratings definitions on page 4.
Ratings at 1.0 power factor.

Technical Data		
Engine Make & Model:	Perkins 1103A-33G1	
Alternator Model:	LLB1014S	
Base Frame Type:	Heavy Duty Fabricated Steel	
Circuit Breaker Type:	3 Pole MCB	
Frequency:	50 Hz	60 Hz
Engine Speed: RPM	1500	1800
Fuel Tank Capacity: litres (US gal)	144 (38.0)	
Fuel Consumption, Prime: l/hr (US gal/hr)	6.9 (1.8)	8.0 (2.1)
Fuel Consumption, Standby : l/hr (US gal/hr)	7.5 (2.0)	9.1 (2.4)

Engine Technical Data

Physical Data	
Manufacturer:	Perkins
Model:	1103A-33G1
No. of Cylinders/Alignment:	3 / In Line
Cycle:	4 Stroke
Induction:	Naturally Aspirated
Cooling Method:	Water
Governing Type:	Mechanical
Governing Class:	ISO 8528 G2
Compression Ratio:	19.25:1
Displacement: l (cu.in)	3.3 (201.4)
Bore/Stroke: mm (in)	105.0 (4.1)/127.0 (5.0)
Moment of Inertia: kg m ² (lb. in ²)	1.14 (3896)
Engine Electrical System:	
-Voltage/Ground:	12/Negative
-Battery Charger Amps:	65
Weight: kg (lb) - Dry:	412 (908)
- Wet:	430 (948)

Air System	50 Hz	60 Hz
Air Filter Type:	Replaceable Element	
Combustion Air Flow:		
m ³ /min (cfm) -Standby:	2.5 (88)	3.0 (106)
-Prime:	2.5 (88)	2.9 (102)
Max. Combustion Air Intake		
Restriction: kPa (in H ₂ O)	6.5 (26.1)	6.5 (26.1)
Radiator Cooling Air Flow:		
m ³ /min (cfm)	69.6 (2458)	90.6 (3200)
External Restriction to		
Cooling Air Flow: Pa (in H ₂ O)	120 (0.5)	120 (0.5)

Cooling System	50 Hz	60 Hz
Cooling System Capacity:		
l (US gal)	10.2 (2.7)	10.2 (2.7)
Water Pump Type:	Centrifugal	
Heat Rejected to Water & Lube Oil: kW (Btu/min)		
-Standby:	14.9 (847)	21.6 (1228)
-Prime:	13.6 (773)	19.1 (1086)
Heat Radiation to Room:		
kW (Btu/min) -Standby:	9.0 (512)	9.7 (552)
-Prime:	8.2 (466)	8.4 (478)
Radiator Fan Load: kW (hp)	0.3 (0.4)	0.5 (0.7)

Cooling system designed to operate in ambient conditions up to 50°C (122°F). Contact your local Olympian dealer for power ratings at specific site conditions.

Lubrication system	
Oil Filter Type:	Spin-On, Full Flow
Total Oil Capacity l (US gal):	8.3 (2.2)
Oil Pan l (US gal):	7.8 (2.1)
Oil Type:	AP1 CG4 15W-40
Cooling Method:	Water

Performance	50 Hz	60 Hz
Engine Speed: RPM	1500	1800
Gross Engine Power: kW (hp)		
-Standby:	31.0 (42.0)	36.5 (49.0)
-Prime:	28.2 (38.0)	33.1 (44.0)
BMEP: kPa (psi)		
-Standby:	752.0 (109.0)	738.0 (107.0)
-Prime:	684.0 (99.2)	669.0 (97.0)
Regenerative Power: kW	7.0	9.0

Fuel System				
Fuel Filter Type:	Replaceable Element			
Recommended Fuel:	Class A2 Diesel			
Fuel Consumption: l/hr (US gal/hr)				
	110% Load	100% Load	75% Load	50% Load
Prime				
50 Hz	7.4 (2.0)	6.9 (1.8)	5.2 (1.4)	3.9 (1.0)
60 Hz	9.0 (2.4)	8.0 (2.1)	6.3 (1.7)	4.8 (1.3)
Standby				
50 Hz		7.5 (2.0)	5.6 (1.5)	4.1 (1.1)
60 Hz		9.1 (2.4)	6.9 (1.8)	5.1 (1.4)

(based on diesel fuel with a specific gravity of 0.85 and conforming to BS2869, Class A2)

Exhaust System	50 Hz	60 Hz
Silencer Type:	Level 1	
Silencer Noise Reduction	SD50 (1)	
Pressure Drop Across		
Silencer System: kPa (in Hg)	1.80 (0.532)	2.00 (0.591)
Silencer Noise Reduction		
Level: dB	20	19
Max. Allowable Back		
Pressure: kPa (in. Hg)	8.0 (2.4)	10.0 (3.0)
Exhaust Gas Flow:		
m ³ /min (cfm) -Standby:	6.2 (219)	7.5 (265)
-Prime:	5.2 (184)	6.3 (222)
Exhaust Gas Temperature: °C (°F)		
m ³ /min (cfm) -Standby:	490 (914)	510 (950)
-Prime:	472 (882)	501 (934)

Alternator Performance Data

Data Item	50 Hz				60 Hz				
	240V 240V/120V	230V 230/115V	220V 220V/110V			220V 220V/110V	240V 240V/120V	230V 230V/115V	
Motor Starting Capability* kVA	54	51	48	-	-	42	47	45	-
Short Circuit Capacity** %	-	-	-	-	-	-	-	-	-
Reactances: Per Unit									
Xd	1.380	1.500	1.640	-	-	2.210	1.860	2.020	-
X'd	0.170	0.180	0.200	-	-	0.270	0.230	0.240	-
X''d	0.075	0.082	0.089	-	-	0.120	0.101	0.110	-

Reactances shown are applicable to standby ratings.

* Based on 30% voltage dip. Improved motor starting capability is available with optional Permanent Magnet generator or AREP excitation.

** With optional Permanent Magnet generator or AREP excitation.

Alternator Technical Data

Physical Data	
Manufacturer:	OLYMPIAN
Model:	LLB1014S
No. of Bearings:	1
Insulation Class:	H
Winding Pitch - Code:	2/3 - M
Wires:	4
Ingress Protection Rating:	IP23
Excitation System:	SHUNT
AVR Model:	R250

Operating Data	
Overspeed: RPM	2250
Voltage Regulation (steady state) (%):	+/- 1.0
Wave Form NEMA = TIF:	50
Wave Form IEC = THF:	2.0%
Total Harmonic Content LL/LN:	4.0%
Radio Interference:	Suppression is in line with European Standard EN61000-6
Radiant Heat: kW (Btu/min)	
-50 Hz:	3.2 (182)
-60 Hz:	3.8 (216)

Consult your Olympian representative for more information

